



## XPS-E

Intelligent PROFIBUS DP - RS232/RS422/RS485 Gateway

### □ Description

This gateway allows you to integrate your serial devices quickly, easily and reliably into a PROFIBUS DP network.

All connected serial devices will work as usual, as our gateway depicts all

send and receive sequences 1:1. The data can be accessed swiftly and exactly.

Moreover, our drivers facilitate a pre-processing of data within the gateway. Of course, our drivers can be

customized according to your requirements.


XPS-E is foreseen for top-hat rail mounting.

### □ Technical Data

<b>Interfaces</b>	Serial RS232/422/485 PROFIBUS RS485 (isolated)
<b>Baud Rate Serial</b>	Max. 38.400 Bit/s asynchronous (adjustable via PROFIBUS)
<b>Baud Rates PROFIBUS DP</b>	9.6, 19.2, 45.45, 93.75, 187.5, 500 Kbit/s and 1.5, 3, 6, 12 Mbit/s (automatic baud rate detection)
<b>DP-Protocol Version</b>	DP Slave (modular 4 - 240 Bytes)
<b>Power Supply</b>	24 VDC



XPS-E



**Order Numbers**

<b>Order No.</b>	<b>Item</b>
4000-7-G 0 1 -H-*	XPS-E for top-hat rail with Universal Driver

\* Please complete the order number either with E for a documentation in English or D for a documentation in German.